

CABLE SPECIFICATIONS



WirelineWorks INC.

"Quality You Can Pull On..."

CABLE SIZE	SIZE (in)	DIAM (in)	B.S. (lbs.)	WEIGHT (lbs.)	ARMOR WIRES IN/OUT	WIRE B.S.-lbs. IN/OUT	STRETCH COEFICIENT ft/kft/lb	CDR RESIS OHMS/MFT	CAP Pf-Ft	MAX TEMP DEG F	MIN SHEAVE DIA (in)	MAX VOLT
1-S-185-PD	3/16	0.185	4,000	65	12/12	109/278	3.00	9.4	53	300	14	1000
1-S-185-TD	3/16	0.185	4,000	67	12/12	109/278	3.00	9.4	63	500	14	1000
1-R-224-PH	7/32	0.224	5,600	94	12/18	212/212	2.50	4.0	59	300	14	1200
1-R-224-TH	7/32	0.224	5,600	97	12/18	212/212	2.50	4.0	68	500	14	1200
1-R-224-FTD-NS	7/32	0.224	4,800	99	12/18	189/189	2.90	6.7	43	500	14	1200
1-R-224-FTD-MP35	7/32	0.224	5,200	100	12/18	212/212	2.90	6.7	43	500	14	1200
1-Z-224-PH	7/32	0.224	5,600	94	15/15	135/275	2.20	4.0	59	300	14	1200
1-Z-224-TH	7/32	0.224	5,600	97	15/15	135/275	2.20	4.0	68	500	14	1200
1-Z-224-FTD-NS	7/32	0.224	4,800	96	15/15	115/250	2.70	6.7	43	500	14	1200
1-Z-224-ATD-MP35	7/32	0.224	5,200	100	15/15	125/275	2.40	6.7	43	500	14	1200
1-R-258-PH	1/4	0.258	7,300	120	12/18	275/275	1.90	4.0	50	300	14	1200
1-R-258-FTH	1/4	0.258	7,300	125	12/18	275/275	1.90	4.0	53	500	14	1200
1-R-288-PH	9/32	0.288	10,000	154	12/18	355/355	1.60	2.8	54	300	16	1500
1-R-288-TH	9/32	0.288	10,000	157	12/18	355/355	1.60	2.8	55	500	16	1500
1-R-322-PH	5/16	0.322	11,200	188	12/18	435/435	1.20	2.8	46	300	18	1500
1-R-322-FTH	5/16	0.322	11,200	195	12/18	435/435	1.20	2.8	45	500	18	1500
1-R-380-PH	3/8	0.380	15,000	259	12/18	597/597	1.00	2.8	39	300	21	1500
1-R-380-FTH	3/8	0.380	15,000	269	12/18	597/597	1.00	2.8	39	500	21	1500
1-R-425-PH	7/16	0.425	18,500	320	12/18	775/775	0.70	2.8	34	300	24	1500
1-R-425-FTH	7/16	0.425	18,500	334	12/18	775/775	0.70	2.8	35	500	24	1500
7-Y-380-PD	3/8	0.378	13,000	254	18/18	290/584	1.40	9.8	64	300	21	1000
7-Y-380-TD	3/8	0.378	13,000	261	18/18	290/584	1.40	9.8	76	500	21	1000
7-Y-428-PD	7/16	0.428	18,300	310	18/18	399/745	0.75	9.8	53	300	23	1000
7-Y-428-TD	7/16	0.428	18,300	319	18/18	399/745	0.75	9.8	62	500	23	1000
7-K-464-PD	15/32	0.464	18,300	321	24/24	335/537	0.77	9.8	40	300	20	1200
7-K-464-FTD	15/32	0.464	18,300	341	24/24	335/537	0.77	9.8	39	500	20	1200
7-Y-474-PD-HS	SLAMMER	0.474	24,300	377	18/18	475/920	0.61	9.8	46	300	27	1200
7-Y-474-FTD-HS	SLAMMER	0.474	24,300	392	18/18	475/920	0.61	9.8	45	500	27	1200

